# **MINI GAC® 2500**

### **GRAIN MOISTURE ANALYZER**

The most accurate handheld moisture tester that provides fast and easy results. Now with 149 MHz - UGMA technology to match the new moisture testers at the elevator.

Measuring grain moisture straight from the field has never been easier than with the DICKEY-john mini GAC® 2500 handheld grain moisture analyzers. This handheld moisture tester offers the highest level of accuracy in its class, plus the mini GAC is fast and easy to use.

#### **Features and Benefits:**

- Simplifies operation with menu-driven interface
- Eliminates pre-weighing with an internal scale
- Avoids cumbersome screw caps that can cause grain damage and oily residue
- Measures over 250 types of grain and product
- Easily loads calibrations with a USB
- Tests hot or cold grain between 32 and 122°F (0 50°C)
- Receives accurate measurements in a variety of conditions with automatic temperature compensation

#### Backed by the power of DICKEY-john:

When you buy a mini GAC 2500, you get all the dependability and value you expect from DICKEY-john products. DICKEY-john's advanced technology and superior electronics are backed by a team of expert, in-house mechanical, electrical, software, and test engineers. All mini GACs are manufactured by DICKEY-john under strict quality control in an ISO 9001 certified facility. Made in the U.S.A.





# **MINI GAC<sup>®</sup> 2500**

#### **GRAIN MOISTURE ANALYZER**



#### **Unit Specifications**

Measurement method: 149 MHz - UGMA technology,

internal scale, temperature

Moisture range: 5 - 45 % (depending on grain type)

Grain temperature: 32 - 122° F (0 - 50° C)

Temperature difference: 36° F (20° C)

instrument to grain sample

Temperature compensation: automatic

Grain type: whole grain, no sample preparation

Sample size: 1 pint (0.47 L)

Display: LCD (106 x 56 pixels)
Analyzer height:\*
Analyzer width:\*
Analyzer depth:\*
Weight (total):

LCD (106 x 56 pixels)
11.9 in (30.2 cm)
4.8 in (12.2 cm)
8.3 in (21.1 cm)
2 lbs 7 oz (1.1 kg)

Measured parameters: moisture, grain temperature

and test weight

Calibrations: 20 grain calibrations (choose

from over 250 calibrations that

are available)

# Grain Temperature Measurement Specification

Accuracy: 1.0° F or 0.5° C
Temperature resolution 0.1° F or 0.1° C

Test Weight Specifications

Repeatability: 0.5 lb/bu (0.6 kg/h)

in commercial trade range, depending on grain type

Test weight resolution: 0.1 lb/bu (kg/hl)

#### **Other Specifications**

Operating temperature: 40 - 113° F (5 - 45° C)
Humidity: 5 - 95% non-condensing
Power: 9 VDC battery (installed)

\* Measured with loader/striker in carrying position.

## Moisture Measurement Specifications

Moisture repeatability: 0.3% moisture, depending on

grain type, in commercial trade

range, typical

Moisture resolution: 0.1% moisture



1. Fill loader



2. Empty loader into analyzer



3. Level grain



4. Press button, results in seconds



Package includes: mini GAC 2500, loader, 9 volt battery, carrying case, belt clip, instruction manual and 1 year manufacturer's warranty



